


60 Cohoes Ave. Green Island, NY 12183 • Ph: (518) 270-2159 • Fax: (518) 270-8384

www.gemlockgrooved.com

FLANGE ADAPTERS - STYLE F190 & STYLE F190 TM

- Conforms to Class ANSI 125 lb. flange
- Available with an external threaded or grooved end
- Every lot is metallurgically tested for compliance
- Available with hot dipped galvanized coating
- Pressure ratings of fittings conform to those of Style 5, Style 12, and Style 25 couplings



Nominal Size (In.)	Actual Size (In.)	E to E (In.)	Approx. Wgt. Ea. (lb.)
2	2.375	4.0	6.6
2½	2.875	4.0	8.8
3	3.500	4.0	11.0
4	4.500	6.0	19.8
5	5.563	6.0	22.0
6	6.625	6.0	28.6
8	8.625	6.0	43.0
10	10.750	8.0	60.5



UL Listed Under File No. EX15591

NOTES:

Allowable pipe end separation is for cut groove pipe for roll groove, figures will be one-half of the values listed at time of initial pressurization.

□ - Bolts and Nuts are galvanized. * - Maximum pressure including surges and maximum end loads from all internal and external forces, to which a joint could be subject under normal working conditions. This rating provides a nominal safety factor of 1.5 times working pressure based on standard weight steel pipe. Maximum working pressure may be subjected to a one time field test of 1.5 times the figures indicated. Refer to installations and groove specifications when assembling any grooved product. For dry systems, TRI Seal gaskets are recommended. EPDM gasket is supplied as standard. For other gaskets contact us.

PROJECT INFORMATION		APPROVAL STAMP	
Project:		<input type="checkbox"/> Approved	
Address:		<input type="checkbox"/> Approved as noted	
Contractor:		<input type="checkbox"/> Not approved	
Engineer:		Remarks:	
Submittal Data:			
Notes 1:			
Notes 2:			