


60 Cohoes Ave. Green Island, NY 12183 • Ph: (518) 270-2159 • Fax: (518) 270-8384

www.gemlockgrooved.com

## DING CTVIE 10

- Provides joint flexibility required in some piping systems
- Conforms to the requirements of ANSI B31.1 Power Piping Code; ANSI B31.9 Building Service Pipe Code and NFPA 13 Sprinkler Systems



Pipe		Max Working	Allow Pipe End	Max Deflection from Center Line §		Dimensions (In.)			Approx. Weight
Nominal Size	Actual Size (In.)	Pressure (psi)*	Separation (in.)§	Per Coup. Deg.	Pipe (In.)	Α	В	С	Each (lb.)
1"	1.315	400	0.10	5°-26'	1.14	2.188	3.858	1.73	1.2
11⁄4"	1.660	400	0.10	4°-19'	0.90	2.535	3.897	1.732	1.3
1½"	1.900	400	0.10	3°-46'	0.79	2.803	4.527	1.732	1.5
2"	2.375	400	0.10	3°-1'	0.62	3.283	5.00	1.732	1.7
2½"	2.875	400	0.10	2°-29'	0.52	3.842	5.433	1.732	2.0
3"	3.500	400	0.10	2°-3'	0.43	4.574	6.535	1.772	2.6
4"	4.500	400	0.16	3°-11'	0.67	5.614	7.598	1.889	4.1
5"	5.563	300	0.16	2°-35'	0.54	6.771	8.818	1.889	5.7
6"	6.625	300	0.16	2°-10'	0.46	7.874	9.921	1.889	6.1
8"	8.625	300	0.19	1°-40'	0.34	10.71	12.637	2.362	11.9
10" *	10.75	300	0.19	0°-95'	0.13	12.91	16.54	2.52	21.5



NOTES:

\*Standard weight coupling

UL Listed Under File No. EX15592

Allowable pipe end separation is for cut groove pipe for roll groove, figures will be one-half of the values listed at time of initial pressurization.

— Bolts and Nuts are galvanized. \* — Maximum pressure including surges and maximum end loads from all internal and external forces, to which a joint could be subject under normal working conditions. This rating provides a nominal safety factor of 1.5 times working pressure based on standard weight steel pipe. Maximum working pressure may be subjected to a one time field test of 1.5 times the figures indicated. Refer to installations and groove specifications when assembling any grooved product. For dry systems, TRI Seal gaskets are recommended. EPDM gasket is supplied as standard. For other gaskets contact us.

PROJECT INFORMATION	APPROVAL STAMP
Project:	☐ Approved
Address:	☐ Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Data:	
Notes 1:	
Notes 2:	