


## STANDARD CONCENTRIC REDUCER STYLE 140



UL Listed  
Under File No. EX15591

- Made of durable, high-strength ductile iron conforming to ASTM A536
- Every lot is metallurgically tested for compliance
- Available with hot dipped galvanized coating
- Rated for 300 psi



See Style 140TM and 140TF for threaded outlet

## ECCENTRIC REDUCER STYLE 145

\* Fabricated

ECCENTRIC REDUCER - NO.145		
Add TF after part number for Internal or TM for External threaded outlet.		
Nominal Size (In.)	E to E (In.)	Approx. Wgt. Ea. (Lb.)
2 x 1-1/4*	9	4.6
2 x 1-1/2*	9	4.6
2-1/2 x 2*	9.5	1.4
3 x 1-1/4*	9.5	4.8
3 x 1-1/2*	9.5	5.0
3 x 2	2.52	1.8
3 x 2-1/2	2.52	1.6
4 x 2	3.00	2.6
4 x 2-1/2	3.00	2.8
4 x 3	3.00	3.3
5 x 2	3.50	5.2
5 x 2-1/2	3.50	10.8
5 x 3	3.50	11
5 x 4	3.50	5.1
6 x 2	4.02	14.5
6 x 2-1/2	4.02	14.1
6 x 3	4.02	14.9
6 x 4	4.02	6.6
6 x 5	4.02	9.4
8 x 3	5.00	22.0
8 x 4	5.00	22.9
8 x 5	5.00	26.5
8 x 6	5.00	30.8
10 x 6	5.98	36.5
10 x 8	5.98	38

CONCENTRIC REDUCER - NO.140			CONCENTRIC REDUCER - NO.140		
Nominal Size (In.)	E to E (In.)	Approx. Wgt. Ea. (Lb.)	Nominal Size	E to E (In.)	Approx. Wgt. Ea. (Lb.)
1-1/4 x 1	2.52	.49	5 x 2-1/2	3.5	2.57
1-1/2 x 1	2.52	.60	5 x 3	3.5	2.73
2 x 1	2.52	.72	5 x 4	3.5	2.95
2 x 1-1/4	2.52	.69	6 x 2	4.02	4.36
2 x 1-1/2	2.52	.72	6 x 2-1/2	4.02	4.10
2-1/2 x 1	2.52	.86	6 x 3	4.02	4.12
2-1/2 x 1-1/4	2.52	.91	6 x 4	4.02	4.63
2-1/2 x 1-1/2	2.52	.92	6 x 5	4.02	4.35
2-1/2 x 2	2.52	1.02	8 x 3	5	7.71
3 x 1	2.52	1.10	8 x 4	5	6.76
3 x 1-1/4	2.52	1.15	8 x 5	5	7.71
3 x 1-1/2	2.52	1.16	8 x 6	5	8.15
3 x 2-1/2	2.52	1.25	10 x 4	5.98	20.0
4 x 1	3.00	2.2	10 x 5	5.98	20.0
4 x 1-1/4	3.00	2.2	10 x 6	5.98	14.48
4 x 1-1/2	3.00	2.3	10 x 8	5.98	14.16
4 x 2	3.00	2.4	—	—	—
4 x 2-1/2	3.00	2.7	—	—	—
4 x 3	3.00	2.8	—	—	—
5 x 2	3.5	3.8	—	—	—

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	